

TECHNICAL DATA

T 81840



STATIONARY COMPRESSOR UNITS - MAX. 10 BAR.

Designation	Receiv. volume	*) F.A.D. l/min.	R.P.M	Motor		Dimensions in mm			Weight kg	D-O-L- Starter	Star/ Delta Starter
				kW	HK	l	b	h			
PL30	50	234	1252	2,2	3,0	910	410	750	75	✓	
PL30	90	234	1252	2,2	3,0	1100	430	840	90	✓	
PL50	90	374	1228	3,0	4,0	1100	430	840	95	✓	
PL50	150	374	1228	3,0	4,0	1250	470	970	110	✓	
PL75	190	637	962	4,0	5,5	1460	550	1050	180	✓	
PL75	280	637	962	4,0	5,5	1690	580	1100	210	✓	
PL75	500	637	962	4,0	5,5	1950	610	1230	240	✓	
PL75	190	715	1080	5,5	7,5	1460	550	1050	220	✓	✓
PL75	280	715	1080	5,5	7,5	1690	580	1100	245	✓	✓
PL75	500	715	1080	5,5	7,5	1950	610	1230	275	✓	✓
PL100	190	989	1094	7,5	10,0	1460	550	1050	240	✓	✓
PL100	280	989	1094	7,5	10,0	1690	580	1100	265	✓	✓
PL100	500	989	1094	7,5	10,0	1950	610	1230	295	✓	✓

- Free air delivery at 50° C, absolute inlet pressure 1 bar and inlet temperature 20° C.
Working pressure of the compressor 80% of max. pressure

No liability accepted for specifications which are subject to alteration.



STENHØJ

☎ +45 7682 1260
 Fax +45 7682 1282
 Internet www.stenhoj.dk
 E-mail: kompresor@stenhoj.dk

TECHNICAL DATA

T 81841



PORTABLE COMPRESSOR UNITS - MAX. 10 BAR.

Designation	Receiving volume	*) F.A.D. l/min.	R.P.M	Motor		Dimensions in mm			Weight kg	D-O-L-Starter	Star/Delta Starter
				kW	HK	l	b	h			
PL30	50	235	1250	2,2	3,0	1080	620	760	90	✓	
PL30	90	235	1250	2,2	3,0	1270	620	830	105	✓	
PL50	90	370	1225	3,0	4,0	1270	620	840	110	✓	
PL50	150	370	1225	3,0	4,0	1280	700	960	120	✓	
PE50B	90	340	970	3,0	4,0	1280	620	900	150	✓	
PE50B	150	420	1050	4,0	5,5	1280	700	950	170	✓	
PL75	150	540	960	4,0	5,5	1280	700	1050	155	✓	

- Free air delivery at 50° C, absolute inlet pressure 1 bar and inlet temperature 20° C.
Working pressure of the compressor 80% of max. pressure

No liability accepted for specifications which are subject to alteration.



STENHØJ

☎ +45 7682 1260
 Fax +45 7682 1282
 Internet www.stenhøj.dk
 E-mail: kompresor@stenhøj.dk

TECHNICAL DATA

T81842



VERTICAL COMPRESSOR UNITS - MAX. 10 BAR.

Designation	Receiver volume	*) F.A.D l/min.	R.P.M	Motor		Dimension in mm			Weight kg	D-O-L Starter	Star/Delta Starter
				kW	HK	d	b	h			
PE50B	275	420	1050	4,0	5,5	710	970	1750	265	✓	
PL75	275	540	960	4,0	5,5	710	1030	1750	245	✓	
PL75	275	715	1050	5,5	7,5	710	1030	1750	250		✓
PL100	275	900	1100	7,5	10,0	710	1060	1760	255		✓

- Free air delivery at 50° C, absolute inlet pressure 1 bar and inlet temperature 20° C. Working pressure of the compressor 80% of max. pressure.

No liability accepted for specifications which are subject to alteration.



STENHØJ

+45 7682 1260

Fax +45 7682 1282

Internet www.stenhøj.dk

E-mail: kompressor@stenhoj.dk