

11,0 t, 750 mm Pit Jack FHZ 11/750



telescopic transmission jack, running on the floor side- and lengthwise, suitable for lifting HGV's/Buses at the axle or frame resp. for removal of aggregates (e.g. transmissions)

**description:**

Hydraulic-pneumatic pit jack, running on the floor, ideal for inspection pits, also in combination with integrated roller brake tester, the jack can move beside the rollers protruding into the pit, also suitable for lifting trucks and bus axles,

- pneumatic high-speed control "up" in unladen condition
- pneumatic forced ram retraction of cylinder (deadman control)
- load lifting by pump, automatic load lifting on option
- easily accessible release valve (rapid ram approach/forced ram return)
- freely movable spring-loaded carriage "FF" with easy-running poly-rollers thereby the jack can be easily moved side- and lengthwise inside the pit up to a load of 1.000 kg, with a higher load than 1.000 kg the carriage blocks automatically and ensures safe lifting,
- carriage size 1.000 mm long x 800 mm wide
- incl. service-unit

**technical details:**

Capacity	11.000 kg
Lifting height max.	1.825 mm
Stroke	750 mm
ø Piston	60 mm
ø Pad	45 mm
Overall height	1.075 mm
Overall width-/ length	800x1.000 mm
Air supply	8 bar
Control	hydraulic/pneumatic
Carriage	"FF" freel
Weight	104 kg

Artikel-Nr.: FHZ 11/750