

30 t Mobile Column Lift RGE 4.30/1750



Mobile column lift for fork lifters with 4 mobile single columns and universal carriage with fixed forks

description:

specification of each lift:

- ◆ mechanical dolly with 2 rollers
- ◆ remote cable control with emergency-stop for operating the entire lift or single-mode operation, connectable at each column.
- ◆ mobile supply unit for the main terminal, connectable at each column.

specification of each column:

- ◆ splash-proof control box with push-button for single-mode operation.
- ◆ quick interconnection of columns by ring circuit
- ◆ electronic synchronisation and safety monitoring
- ◆ non-contact distance measuring by inductive travel sensors
- ◆ low-friction recirculating ball screw (efficiency over 90 %)
- ◆ mechanical emergency lowering in case of power failure
- ◆ powder painting RAL blue 5015, anthracite 7016

technical details:

| | |
|---------------------|--------------------------|
| Capacity | 4 x 7.500 kg |
| Lifting height max. | 1.750 mm |
| Lifting time | 113 sec |
| Synchronisation | electronical |
| Power drive | 2 x 1,5 kW |
| Operating voltage | 3 x 400/250 / 50 Hz V/Hz |
| Control voltage | 230/24 /50 V/Hz |
| Fuse protection | 8 slow A Träge |
| Weight | 800 kg |

Artikel-Nr.: RGE 4.30/1750